



Model : KOT-0156U-CA4PH

V 2.0

Open Frame Touch Monitor

- KeeTouch water proof capacitive sensor allows wet finger operation, provides high quality touch experience even in harsh environment.
- High Brightness, visible under direct sunlight.
- Vandal proof IK06
- Anti-glare tempered cover glass.
- IP65_(front surface).

Specification

Complete Machine		
Model No.	KOT-0156U-CA4PH	
Series	OT	
Display Type	16 : 9 , 15.6" TFT-LCD,LED backlight	
Active Area	345.8*195.2 (mm)	
Monitor Dimensions (W*H*D)	394.6*251*52 (mm)	
Suggested Resolution	1920*1080 @ 60Hz	
Support Colors	16.2M	
Brightness (Typ.)	Pure LCD Panel	1000cd/m2
	With Touch Monitor	830cd/m2
Response Time (Typ.)	12ms	
Viewing Angle(Typ.at CR > 10)	Horizontal(left/right)	85°/85°
	Vertical(up/down)	85°/85°
Contrast Ratio (Typ.)	800:1	
Video Input	VGA/HDMI	
Frequency (H/V)	40 ~ 90KHz / 50 ~ 60Hz	
Power Supply	Type: External brick Display voltage: DC 12V±5% Input (line) voltage: 100-240 VAC, 50-60 Hz	
Environment	Operating Temp.	-10 ~ 60°C
	Operating RH	20% ~ 80%
	Storage Temp.	-20 ~ 70°C
	Storage RH	10% ~ 90%
MTBF	50,000 Hours	
LED Back Light Life (Typ.)	50,000 Hours	
OSD Control	Buttons	AUTO,+,POWER,-,MENU
	Function	Brightness, Contrast Ratio, Auto-adjust, Phase, Clock, H/V Location, Languages, Function, Reset
Agency approvals	CCC, ETL, FCC, CE, CB, RoHS	
Touch screen Type	15.6" Projected Capacitive Touchscreen	
Touch System Interface	USB	
Support System	10 points in win7	
Regular Warranty	1 year	

NOTE :

The display SPEC. are adjusted according to the selected LCD screen and touch screen

The support system is adjusted according the specific system and version.

Mechanical Dimensions

